

QVBC.SA45820 - Commercial Refrigeration Recovery/Recycling Equipment Certified for Performance Characteristics in Accordance with the United States Clean Air Act

NAVAC Inc.1099 Wall St W Ste 179

Lyndhurst, NJ 07071-3624 United States

Certified for performance in accordance with EPA's Minimum Requirements for Recycling or Recovery Equipment.

Performance Data

Model Dsg	Refrigerant	Push/Pull Recovery Rate (kg/min)	Liquid Recovery Rate (kg/min)	Vapor Recovery Rate (kg/min)	Final Recovery Vacuum Level kPa	Moisture Content (ppm by weight)	Chloride lons (ppm by weight)	Acidity (ppm by weight)	High Boiling Residue (% by volume)	Particulates Solids Visual	Non- condensable Purge Loss (<3% by weight)	Refrigerant Loss, Weight %	Residual Trapped Refrigerant kg	High Temp (104 F) Vapor Recovery Rate (kg/Min)
"NRDC4M"	R22	7.6	5.79	0.45	50.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.011	0.46
	R134a	6.84	4.17	0.38	50.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.008	_
	R407C	8.51	5.98	0.45	50.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.008	_
	R410A	8.27	7.63	0.48	50.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.016	_

^{*} Product identification, construction variations, ratings and performance data.

iq.ulprospector.com/en/profile?e=4605085